



The new and improved 44 & 62 Ultra Plus are the ultimate first time roller laminators. The inclusion of twin heated rollers and a powered rewind station ensures these machines are the ideal, easy to use, highly capable solution. The 44 & 62 Ultra Plus now deliver professional performance and results at an affordable price.

Capable of mounting, laminating and encapsulating prints up to 1115 mm (1550 mm for the 62 Ultra Plus) and handling a range of substrates up to 12,5 mm, the 44 & 62 Ultra Plus provide cost effective finishing solutions for a wide range of digitally and photographically produced graphics.

The 62 Ultra Plus now incorporates a roll capture mechanism making the handling of the wider and heavier 1550 mm wide

material easier. This simple device supports the weight of the roll allowing the operator to easily engage the roll locking mechanism.

With their compact design and broad application ability the SEAL 44 & 62 Ultra Plus are suitable for businesses wishing to introduce application solutions to their customers or desiring to complement existing lamination facilities.

### The SEAL 44 & 62 Ultra provide the following features

#### Optimum performance

- Twin heated rollers, switchable for top heat only if required
- 3 temperature settings 50°C, 90°C, 120°C for use with different films and adhesives
- Maximum speed of 2,13 m/min runs quicker than any inkjet printer
- Foot control for hands free operation and precise media/substrate feed
- Maximum nip opening of 12,5 mm for processing of most popular substrates
- 1115 mm & 1550 mm working widths cover majority of the inkjet market

#### Ease of use

- Simple touch pad control panel
- Quick reference guide on machine for application advice
- Adjustable speed dial allowing user control of settings
- Powered upper rewind station
- Easy to clean silicon coated rollers prevent sticking of materials
- Auto-grip shafts for easy loading of materials
- No special power requirements for plug and play
- Robust castors for easy movability of machine

#### Safety

- Comprehensive safety system with emergency stops and self-checking safety eyes
- Roll capture mechanism on the 62 Ultra Plus
- CE/ETL certified


Rigid Indoor Displays




Flexible Indoor Displays



Floor Graphics



Backlit Displays



Pop-Up Displays



Rigid Outdoor Displays



# SEAL 44 & 62 Ultra Plus

## Technical Specifications

	44 Ultra Plus	62 Ultra Plus
Maximum Working Width	1115 mm	1550 mm
Maximum Speed	2,13 m/min.	2,13 m/min.
Maximum Substrate Thickness	12,5 mm	12,5 mm
Maximum Roller Temperature	120°C	120°C
Roller Heating	Dual	Dual
Width	1480 mm	1940 mm
Height	1110 mm	1110 mm
Depth	570 mm	570 mm
Net Weight	110 kg	140 kg
Shipping Dimensions	Width	1000 mm
	Height	720 mm
	Depth	630 mm
Shipping Weight	135 kg	189 kg
Electrical Requirements	Single Phase	Single Phase
	230VAC	230VAC
	50/60 Hz	50/60 Hz
	9A	13A
Order Code	64140	64142

SEAL® is a registered trademark of SEAL Graphics

Powered upper rewind station.



1. Single control knob enabling adjustment of substrate thicknesses.
2. Simple control panel showing temperature and speed adjustments.
3. On/off switch for bottom heater.



Roll capture mechanism on the 62 Ultra Plus.



### SEAL Graphics Europe

Heesweg 16A  
8102 HJ Raalte  
The Netherlands  
Tel: + 31 572 346 000  
Fax: + 31 572 346 001  
Customer services:  
Tel: + 49 5722 2070

### SEAL Graphics UK

1 Watkins Close  
Burnt Mills Industrial Estate  
Basildon, Essex SS13 1TL  
United Kingdom  
Tel: + 44 1268 722 400  
Fax: + 44 1268 725 864

### SEAL Graphics Asia

Room 2004-2005, 20th Floor,  
Cable TV Tower, 9 Hoi Shing Road,  
Tsuen Wan, New Territories  
Hong Kong  
Tel: + 852 2407 3738  
Fax: + 852 2408 0973

### SEAL for the Americas

7091 Troy Hill Drive  
Elkridge  
MD 21075  
U.S.A.  
Tel: + 1 410 379 5400  
Fax: + 1 410 579 8960



Contact your local distributor: